

# Robotic Arm CB10L



## Features:

1. Top speed: By using light-weight arms and small sized motors, the fastest speed and acceleration is greatly enhanced. In addition, by adjusting acceleration of load and orientation, optimal continuous performance is fulfilled and cycle time is greatly reduced.
2. Tiny wrist and high torque: Compact wrist realizes free operation in narrow space. In addition, by adopting high output rotational torque and high rotating speed small-sized motors as well as enhancing wrist stiffness to raise the wrist loading capacity. The selection range of gripper, tool, and workpiece shape is also broadened.
3. Large area operation range: Besides maximum operation range, it also broadens the area of the all the axes. Thus expansion of the lower region and main body neighboring region action range is realized. The layout freedom is also raised.
4. Good environment adaptability: Each joint adopts double layer sealing structure and water proof interface so that the wrist part Ingress Protection Rating and basic axis Ingress Protection Rating reach IP67 and IP65 respectively.
5. High expandability: In the process of selecting accessories, built-in solenoid valve and detecting cable are applied so that the application of peripheral robotic arms, loading and unloading becomes easier. Moreover, standard cable bracket installation screw holes are configured in each axis of the robotic arm so that additional tubing and wiring can be achieved later on.

## Product Specifications

Function		Description
Model		CB10L
Arm format		Vertical multi-joint
Controlled axes		6 Axis
Maximum payload (kg)		10Kg
Maximum motion range (°)	Rotation	±180°
	Horizontal arm	+155°~-105°
	Vertical arm	+150°~-163°
	Inner wrist	±270°



	Wrist bend	±145°
	Wrist turn	±360°
Maximum speed (°/sec.)	Rotation	190°/s
	Horizontal arm	205°/s
	Vertical arm	210°/s
	Inner wrist	400°/s
	Wrist bend	360°/s
	Wrist turn	610°/s
Allowable moment (N·m)	Inner wrist	22N·m
	Wrist bend	22N·m
	Wrist turn	10N·m
Allowable moment of inertia (kg·m <sup>2</sup> )	Inner wrist	0.7kg·m <sup>2</sup>
	Wrist bend	0.7kg·m <sup>2</sup>
	Wrist turn	0.2kg·m <sup>2</sup>
Repeatability (mm)		±0.06mm
Reach		1925mm
Resultant maximum speed		13100mm/s
Weight		230kg
Mounting positions		Floor, Top
Environment	Ambient temperature	0° ~ 45°C
	Relative humidity	35 ~ 85%, , non-condensing
IP Protection		IP65
Power rating		5.6kVA
Corresponding controller		EC03

### Ordering Information

Model No.	Descriptions
CB10L	Robotic arm CB10L



GOOGOL TECHNOLOGY (HK) LIMITED  
Unit 1008-09, 10/F C-Bons International Center, 108  
Wai Yip Street, Kwun Tong, Kowloon, Hong Kong  
Tel.: +(852) 2358-1033  
Fax: +(852) 2719-8399  
E-mail: hkgoogol@gmail.com / sales@googoltech.com  
Web: http://www.googoltech.com

GOOGOL TECHNOLOGY (SZ) LIMITED  
Room W211, IER Building (PKU-HKUST High-  
tech Industrial Park, Nanshan District, Shenzhen,  
PRC (Postal Code: 518057)  
Tel.: +(86) 755-26970817, 755-26970824,  
Fax: +(86) 755-26970821  
E-mail: googol@googoltech.com  
Web: www.googoltech.com.cn

GOOGOL TECHNOLOGY (TWN) LIMITED  
2F., No. 22, Ln. 10, Fuzhong 2nd St., Xitun  
Dist., Taichung City 407, Taiwan  
Tel.: +(886) 4-2358-8245  
E-mail: twinfo@googoltech.com  
Web: http://www.googoltech.com

www.googoltech.com

